

表 今回適用除外が発表された品目を含むHTSコードの、追加関税リストごとの輸入額トップ10

(単位:100万ドル)

リスト	HTSコード	輸入額 (2018年)	USTRによる適用除外となる製品の詳細
1	8544.30.0000	493.08	Wiring sets for golf carts with electric motor for propulsion
	8803.30.0030	491.05	Gearhead assemblies and parts thereof, for use in civil aircraft other than by the Department of Defense or the United States Coast Guard, each valued not over \$90
			Output carriers, of passivated stainless steel, having a gear measuring 36.754 mm in length and 33.782 mm in diameter, with 17 teeth each of a maximum circular thickness of 0.8306 mm, of a kind used in a gearhead assembly for the high-lift system of aircraft, for use in civil aircraft other than by the Department of Defense or the United States Coast Guard
	8431.49.9095	407.97	Snow plow blades and frames therefor
	8421.21.0000	313.51	Water filtering apparatus, each valued not over \$1.50
	8536.50.9065	287.35	Rocker switches, for a current of 16 A or more but not exceeding 20 A
			Switches for domestic clothes dryers, valued over 35 cents but not over 40 cents each
			Switches incorporated into latches for domestic appliances, valued over \$ 0.90 but not over \$1.25 each
	8481.90.9060	259.11	Foot valve housings, of a kind incorporated in paint spraying apparatus, with no external measurement greater than 5 cm
	8544.70.0000	256.96	Digital optical fiber cables, with connectors, of a length exceeding 0.5 m but not exceeding 4.0 m
9013.80.7000	240.98	Flexible pressure sensitive LCD panel display devices used as a surface for electronic writing	
8504.40.4000	212.00	Speed drive controllers for electric motors, designed for use in vehicles using electric motors for propulsion, including but not limited to material handling equipment, golf carts, sweeper scrubbers and aerial lifts, with a value of \$50.00 or more but not exceeding \$700.00	
8443.99.2050	199.54	Stapler-stackers of printer units of subheading 8443.32.10, and parts thereof	
2	8542.31.0001	1,674.19	Application specific integrated circuits (ASICs), not containing memories, designed for use in engine control units (ECUs) to interface with linear exhaust gas oxygen sensors (UEGOs)
	8543.70.9960	1,446.11	Electrical control devices which modulate electrical signals, not containing two or more apparatus of 8535 or 8536, each valued over \$60 but not over \$70
	7308.90.9590	707.99	Driveway gates and pedestrian gates of galvanized steel
	8536.30.8000	333.19	Ground Fault Circuit Interrupters (GFCIs), Appliance Leakage Current Interrupters (ALCIs), Leakage Current Detection Interrupters (LCDIs), and Arc Fault Circuit Interrupters (AFCIs)
Surge protectors of a kind designed to protect a buried-wire pet containment system and its control apparatus, having an energy absorption rating at 120 V of less than 500 joules and 15 A			

リスト	HTSコード	輸入額 (2018年)	USTRによる適用除外となる製品の詳細
2	8501.31.4000	306.29	DC electric motors, 12 V, with an output exceeding 74.6 W but not exceeding 735 W, with lead wires and electrical connector, measuring not over 75 mm outside diameter, with a housing not over 100 mm in length and a shaft not over 60 mm in length
			DC electric motors, 12 V, with an output not exceeding 515 W, measuring not over 95 mm in outside diameter, not over 155 mm in length and with a shaft not over 30 mm in length
			DC electric motors, 120 V, with an output not exceeding 140 W, measuring not over 45 mm in diameter and not over 100 mm in length
			DC electric motors, 120 V, with an output not exceeding 90 W, measuring not over 90 mm long by 35 mm wide by 35 mm high
			DC electric motors, 13.5 V, with an output not exceeding 110 W, measuring not over 75 mm outside diameter, housing not over 120 mm long, a shaft not over 55 mm long and with a mounting flange not over 150 mm
			DC electric motors, 230 V, with an output not exceeding 140 W, measuring not more than 45 mm in diameter and not over 100 mm in length
			DC electric motors, 230 V, with output not exceeding 85 W, measuring not more than 90 mm in length by 35 mm in width by 35 mm in height
			DC electric motors, 24 V, with an output exceeding 74.6 W but not exceeding 735 W, with mounting plate, lead wires and electrical connector, measuring not over 80 mm outside diameter, housing not over 150 mm in length and shaft not over 95 mm in length
			DC electric motors, 24 V, with an output not exceeding 105 W, measuring not over 260 mm in length by 205 mm in width by 825 mm in height
			DC electric motors, 24 V, with an output not exceeding 515 W, measuring not over 95 mm in outside diameter, not over 155 mm in length and with a shaft not over 30 mm in length
			DC electric motors, with an output exceeding 74.6 W but not exceeding 735 W, containing lead wires and an electrical connector
			DC electric motors, with an output exceeding 74.6 W but not exceeding 80 W, each with a pinion gear, valued not over \$5
			DC motors with a power output exceeding 74.6 W but not exceeding 230 W, measuring less than 105 mm in diameter and 50 mm or more but not over 100 mm in length
			DC motors, of an output exceeding 74.6 W but not exceeding 735 W, each valued not over \$18
			Direct Current (DC) permanent magnet motors rated at 90 W or more but not over 110 W and 24 V with torque of 65 Newton meters (Nm) and 2,035 Nm, incorporating a wheel that can manually actuate a valve
			Resin-encapsulated DC permanent magnet brushless motors, with an output of 150 W or more but not exceeding 250 W, designed for use in air conditioning and heat pump systems, measuring 112 mm in diameter and 110 mm or more but not exceeding 122 mm in length (excluding shafts)
			8541.10.0080
9025.19.8080	209.79	Galileo thermometers	
		Handheld electronic thermometers, with a metal thermo-couple probe measuring 10 cm in length	
		Thermometers, not combined with other instruments, other than liquid-filled for direct reading, other than pyrometers, other than clinical thermometers	
3910.00.0000	177.56	Silicone presented in 210 liter (55 gallon) drums or 1,040 liter (275 gallon) intermediate bulk containers (IBCs)	
8536.50.7000	168.48	Electronic AC passive infrared (PIR) motion sensing switches	
		Fixed set-point pressure switches	
		Humidity triggered switches	
		Occupancy and vacancy sensor switches	
		Retro-reflective infrared beam switches consisting of an infrared LED emitter and detector in a single housing and a reflective disk for mounting at a distance; such emitter-detector units operating at no more than 40 V AC/DC and containing a relay or other switching component to open or close a separate (secondary) circuit	
Wall-mountable dimmer switches			
8501.10.6060	153.96	Cylindrical DC electric motors, of an output of 18.65 W or more but not exceeding 37.5 W	
		Swing-gate openers comprising a DC motor with an output of 18.65 W or more but less than 35 W, each including an AC power transformer, a wireless remote-control, an electric linear actuator and an emergency key for disconnecting the actuator	

(注) HTSコードが合致していても、USTR記述による製品詳細に合致しなければ関税の適用除外とはならない

(出所) USTR発表資料、米国国際貿易委員会のデータベースを基に作成